

# Air Craft Warning Light

## Flame proof ( Type d )

### NMWL Series



#### Application

NMWL series of Flame proof warning lights are intended for use in areas made potentially hazardous by the presence of flammable liquid, dust, gas or vapor ( zone 1 or zone 2 ).  
For installation at petroleum refineries, chemical and petrochemical plants, marine locations and process industries where a similar hazard exists.

#### Features

- Full certificate of conformity for group IIC areas
- Used with any lamp suitable for E27 lamp holder or with long life low power consumption LED
- Normally with red glass. Other colors are supplies on request
- Borosilicate glass globe resistant to sudden heat changes and impact is sealed onto a threaded metal base
- Stainless steel wire guard
- Standard internal & external M6 earth stud



**Material :** Copper free aluminum alloy body (BS1490)

**Finish :** Standard : Aluminum natural  
Optional : Epoxy paint, or electrostatic powder coated

CE ATEX

**Approvals:** IEC 60079-0 : 2004, IEC 60079-1 : 2003  
IEC 61241-0 : 2004, IEC 61241-1 : 2004  
ISSeP Certificate No. ISSeP07ATEX022  
CE Ex II 2 G D / Ex d IIC T4 or T3 / Ex tD A21 IP65 T130 °C or T195 °C

NM SWITCHGEAR

نور محور فارس

## Protection Grade

IP65 – Application of an approved non-hardening grease will give added resistance to the ingress of dust and moisture – IP66

## Thread Standards

ISO metric 965.1,  
NPT ANSI B1.201.1,  
ISO 228.1 (G), or  
DIN 40430 (PG).

## Mounting

Various installation attachment and relay control box can be supplied upon request. Please specify at ordering.

